

(19) World Intellectual Property Organization  
International Bureau




(43) International Publication Date  
25 July 2002 (25.07.2002)

PCT

(10) International Publication Number  
**WO 02/058414 A1**

- (51) International Patent Classification<sup>7</sup>: **H04Q 7/20**
- (21) International Application Number: **PCT/KR02/00085**
- (22) International Filing Date: **18 January 2002 (18.01.2002)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
2001/3409 20 January 2001 (20.01.2001) **KR**  
2001/43465 19 July 2001 (19.07.2001) **KR**
- (71) Applicant (for all designated States except US): **SAM-SUNG ELECTRONICS CO., LTD [KR/KR]; 416, Maetan-dong, Paldal-gu, Suwon-shi, 442-370 Kyungki-do (KR).**
- (72) Inventor; and  
(75) Inventor/Applicant (for US only): **KIM, Jong-Hwan [KR/KR]; 117, Chongja-dong, Puntang-gu, Songnam-shi, 463-010 Kyonggi-do (KR).**
- (74) Agent: **LEE, Keon-Joo; Mihwa Bldg. 110-2, Myongryun-dong 4-ga, Chongro-gu, Seoul 110-524 (KR).**
- (81) Designated States (national): **CN, US.**
- (84) Designated States (regional): **European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).**
- Published:**  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **SYSTEM AND METHOD FOR REMOTELY CONTROLLING A MOBILE TERMINAL**



(57) Abstract: Disclosed is a system for remotely controlling a mobile terminal in a mobile communication system. The mobile terminal receives a control command through a call link and performs an operation according to the received control command. An Internet service provider including a remote control emulator transmits a mobile terminal remote control command to the mobile terminal through the call link, upon receipt of the mobile terminal remote control command through a user interface of the remote control emulator.

- 1 -

## SYSTEM AND METHOD FOR REMOTELY CONTROLLING A MOBILE TERMINAL

### ACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates generally to a system and method for controlling a mobile terminal in a mobile communication system, and in particular, to a system and method for remotely controlling a mobile terminal.

#### 2. Description of the Related Art

In general, a mobile communication system provides a short message service (SMS) in which a user can transmit/receive a short message comprised of characters and numbers through a mobile terminal (or mobile station (MS)). A length of the message is restrictive. The SMS uses a data burst message based on a mobile communication protocol such as IS-95A, J-STD-008, IS-95B and IS-2000.

FIG. 1 illustrates a conventional network configuration for providing a short message service. Referring to FIG. 1, a BSC/BTS (Base Station Controller/Base station Transceiver System) 109 establishes a radio link to a mobile terminal (or mobile station (MS)) 111 within its service area (or coverage), and exchanges voice and data with the mobile terminal 111. Although the base station controller (BSC) generally controls a plurality of base stations, FIG. 1 shows that the base station controller controls only two base stations, for simplicity. In the following description, the BSC/BTS will be referred to as a "base station (BS)" for short. The base station 109 is connected to a mobile switching center (MSC) 107 connected to a public switched telephone network (PSTN) 113. The MSC 107 includes a visitor location register (VLR), and though not illustrated, is also connected to other MSCs. A home location register (HLR) 105 has subscriber authentication information and location information of the mobile terminals. A message center (MC) 103 provides additional services such as a voice mail service and the SMS service. Although the MC 103 is connected to the single MSC 107 in FIG. 1, it can also be connected to a plurality of MSCs. An SMS server 101 stores SMS messages to be transmitted to the mobile terminals. When there is an SMS message to be transmitted to the mobile terminal 111 or 117, the MC 103 either transmits the SMS message to the mobile terminal 111 through the HLR 105, or detects a location of the mobile terminal 117 and then

- 2 -

transmits the SMS message along with an MAP (Mobile Application Part) message to the MSC 107 connected to the corresponding mobile terminal 117. The MSC 107 then transmits the SMS message to the mobile terminal 117 through the corresponding base station 115.

5

The mobile terminals should have an algorithm, called an "SMS message task", for transmitting/receiving the SMS messages, and also have a specific key for accessing the SMS service in order to read a received SMS message or transmit an SMS message, and an icon indicating arrival of an SMS message. The SMS message task is commonly performed in association with an EEPROM (Electrically Erasable and Programmable Read Only Memory) database task for managing storage and deletion of data, and a diagnostic monitor task. Commonly, a search task is awaked (or activated) in response to Service Option 6, and then performs a corresponding operation.

15

FIG. 2 illustrates a structure of an SMS protocol stack among a mobile terminal, a base station and a message center in a general mobile communication system. An SMS message is formed based on an IS-95A, IS-95B, IS-2000 or J-STD-008 data burst message. The data burst message is transmitted over a paging channel and a forward traffic channel in a forward link, and transmitted over an access channel and a reverse traffic channel in a reverse link. During a call, the mobile communication system operates in a multiplex option (or mode) where data transmission is available during a voice call.

20

As illustrated in FIG. 2, the mobile terminal (BS) and the message center (MC) have the same layers. The layers include SMS teleservice layers (201 and 221), SMS transport layers (203 and 223), SMS relay layers (205 and 225), and link layers (207 and 227). The link layer 207 of the mobile terminal is based on IS-95A, while the link layer 227 of the MC is based on common channel signaling system No. 7. The base station (BS) has a structure for interfacing signals from the mobile terminal and the MC.

25

30

The associated layers of the mobile terminal and the MC have the same operations, so only the layers of the mobile terminal will be described for simplicity. As illustrated in FIG. 2, an SMS message is carried by a data burst message through the link layer 207. The relay layer 205 receives a message from the transport layer 203 and transmits the received message to a designated next relay point or a terminal point. Upon failure to transmit the message to the next

35

- 3 -

5 relay point or the terminal point, the relay layer 205 creates an error indicator and transmits the error indicator to the transport layer 203. Further, the relay layer 205 transmits a received message to the transport layer 203. The relay layer 205 controls connection to the link layer 207 of IS-95A, IS-95B, IS-2000 or J-STD-008 protocol stack, in order to relay the message.

10 The transport layer 203 forms a terminal point for message exchange between the MC and the mobile terminal, and assembles a message by receiving bearer data from the teleservice layer 201. More specifically, the transport layer 203 assembles a transport layer message by receiving a message parameter from the teleservice layer 201, and transmits the assembled transport layer message to the relay layer 205 using a proper relay layer service primitive. In addition, upon receipt of an ACK (acknowledgment) in reply to the transmitted messages, the transport layer 203 informs the relay layer 205 of receipt of the ACK. However, 15 upon receipt of an error report from the relay layer 205, the transport layer 203 provides the received error information to the teleservice layer 201. Further, the transport layer 203 receives an SMS message from the relay layer 205 and transmits the received SMS message to the teleservice layer 201. If authentication is enabled in the network, the transport layer 203 performs an authentication 20 procedure specified in IS-637.

25 The SMS teleservice layer 201 supports a fundamental SMS function, using a standard subparameter of an SMS message data parameter from the SMS transport layer 203. When the mobile terminal transmits an SMS user ACK message, the SMS teleservice layer 201 transmits a destination address to the transport layer 203. When the MC has an SMS message to transmit to the mobile terminal and a reply option is set up, the SMS teleservice layer 201 provides this information to the user.

30 FIG. 3 illustrates a message format of each layer in a general SMS protocol stack. Referring to FIG. 3, a link layer 330 is comprised of a data burst message. The data burst message includes a message type field (MSG\_TYPE) 331 indicating a type of the message, an ACK sequence field (ACQ\_SEQ) 333, a message sequence field (MSG\_SEQ) 335, a number field (NUM) 337, an SMS character field (CHARi) 339, and a reserved field 340. An SMS parameter is 35 encapsulated in the character field 339, and the link layer 330 analyzes the character field 339 and transmits the analysis result to an upper layer.

- 4 -

A transport layer 310 is formed through a relay layer 320 based on the character field (CHARi) 339 of the data burst message serving as the link layer 330, as shown in FIG. 3. A transport layer message is comprised of an SMS message type field 311 indicating a type of the SMS message, a teleservice identifier field 313 indicating a voice mail service or a normal message service, an originating address field 315, a bearer reply option field 317 indicating a reply request, and a bearer data field 319. The bearer data field 319 is composed of a message of a teleservice layer 300. The teleservice layer message is comprised of a message identifier field 301, a user data field 303 filled with the contents of a received message, an MC time stamp field 305 indicating an MC time of the message, a priority indicator field 306, a privacy indicator field 307, an alert or delivery field 308 for alerting arrival of a message, and a language indicator field 309.

However, the mobile terminal supporting the SMS service becomes useless, when it is missing or not carried by the user. A future mobile terminal will store a great amount of important personal information in it. However, the user cannot remotely access the information stored in the mobile terminal. In other words, the user cannot access the information unless he or she carries the mobile terminal. Therefore, there is a demand for a method of remotely controlling the mobile terminal.

## SUMMARY OF THE INVENTION

It is, therefore, an object of the present invention to provide a system and method for enabling a user to control a mobile terminal even at a remote place, using available communication media.

It is another object of the present invention to provide a system and method for enabling a user to control a mobile terminal and read information from the mobile terminal through an Internet service provider at a computer remote from the mobile terminal.

It is further another object of the present invention to provide a service capable of mutual remote control between mobile terminals by applying an IS-95A, J-STD-008, IS-95B, IS-2000 or IS-637 mobile communication protocol and mobile terminal software, and provide a system and method for enabling a second mobile terminal to remotely control all of the functions provided by a first mobile

- 5 -

terminal, using the service.

5 To achieve the above and other objects, there is provided a system for remotely controlling a mobile terminal in a mobile communication system. The mobile terminal receives a control command through a call link and performs an operation according to the received control command. An Internet service provider including a remote control emulator transmits a mobile terminal remote control command to the mobile terminal through the call link, upon receipt of the mobile terminal remote control command through a user interface of the remote control emulator. The mobile terminal operates based on an IS-637+ layer structure in which a remote control layer exists on a teleservice layer.

10

### BRIEF DESCRIPTION OF THE DRAWINGS

15 The above and other objects, features and advantages of the present invention will become more apparent from the following detailed description when taken in conjunction with the accompanying drawings in which:

FIG. 1 illustrates a conventional network configuration for providing a short message service;

20 FIG. 2 illustrates a structure of an SMS protocol stack among a mobile terminal, a base station and a message center in a general mobile communication system;

FIG. 3 illustrates a layer structure of a general mobile communication system and a message format of each layer;

25 FIG. 4 illustrates a network configuration for providing a remote control service according to an embodiment of the present invention;

FIG. 5 illustrates a layer structure of a mobile communication system and a message format of each layer according to an embodiment of the present invention;

30 FIG. 6A illustrates a format of a user data field of the transport layer, wherein a remote control type field in the remote control message of the mobile terminal is '0001', according to an embodiment of the present invention;

FIG. 6B illustrates a format of the user data field of the transport layer, wherein the remote control type field in the remote control message of the mobile terminal is '0010', according to an embodiment of the present invention;

35

FIG. 7 illustrates a configuration of a remote control software program executed by a remote control application of the mobile terminal according to an embodiment of the present invention;

- 6 -

FIGs. 8A and 8B illustrate an operation implemented by the Client\_T in a mobile communication system which, remotely controls a mobile terminal through a SMS call on a one-side basis according to an embodiment of the present invention;

FIG. 9 illustrates an operation performed by the Server\_T in a mobile communication system, which remotely controls a mobile terminal through a SMS call on a one-side basis according to an embodiment of the present invention;

FIGs. 10A to 10D illustrate states displayed on a screen of the remote control requesting terminal according to an embodiment of the present invention;

FIG. 11 illustrates an operating procedure of the MS web emulator for interactive remote control according to an embodiment of the present invention;

FIG. 12 illustrates an operating procedure of a mobile terminal (Server\_T) for interactive remote control according to an embodiment of the present invention;

FIG. 13 is a ladder diagram illustrating a call process method among a mobile terminal operating in the remote control client mode, an SMS center, an MC, a base station and an MSC according to an embodiment of the present invention;

FIG. 14 is a ladder diagram illustrating a call processing method among a mobile terminal operating in the remote control server mode, an SMS center, a call processing center, a base station and an MSC according to an embodiment of the present invention;

FIGs. 15A to 15C are ladder diagrams illustrating an actual interactive remote control teleservice process according to an embodiment of the present invention; and

FIG. 16 is a ladder diagram illustrating an operation according to an embodiment of the present invention in which a user requests Remote Control End.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A preferred embodiment of the present invention will be described herein below with reference to the accompanying drawings. In the following description, well-known functions or constructions are not described in detail since they would obscure the invention in unnecessary detail.

Remote control of a mobile terminal according to the present invention is divided into a one-sided type and an interactive type. FIGs. 8A, 8B and 9 show the

- 7 -

one-sided remote control, while FIGs. 13 to 16 show the interactive remote control. The remote control of the mobile terminal according to the present invention can be divided into one case where a remote control client terminal (hereinafter, referred to as a "Client\_T") is a computer, and another case where the Client\_T is a mobile terminal.

The interactive remote control service defines a communication protocol for enabling interactive exchange of remote control information between different mobile terminals, and then performs remote control between the mobile terminals using the newly defined communication protocol. In order to perform remote control between the mobile terminals using the existing mobile communication protocol such as IS-95A, J-STD-008, IS-95B, IS-2000, IS-637, and Joint Specification for PCS Terminal Manufacturer-SMS function), the network configuration shown FIG. 1 should be modified.

FIG. 4 illustrates a network configuration for providing a remote control service according to an embodiment of the present invention. Herein, the invention will be described with reference to the interactive remote control service.

In the following description, "Client\_T" represents a remote control requesting terminal. That is, the Client\_T means a mobile terminal 160 or a computer 150, which operates in a remote control client mode at a user's request for remote control. Further, "Server\_T" represents a remote control serving terminal that receives a remote control service request. That is, the Server\_T means a mobile terminal 170, which operates in a remote control server mode upon receiving the remote control service request. For the sake of convenience, the Client\_T and the Server\_T may have different models. In addition, since the mobile terminal provides a different service according to its model, the Client\_T is required to recognize information on the services provided by the Server\_T, in order to control the Server\_T at a remote place. The Client\_T selects a type of service information provided by the Server\_T and transmits the selected service information to the Server\_T, so that the Server\_T is controlled based on the received service information, thus accomplishing the remote control.

If it is assumed that the mobile terminal 160 serves as a Client\_T and the mobile terminal 170 serves as a Server\_T, the system shown in FIG. 4 can remotely control the mobile terminal 170 by accessing a web emulator 145 through the following three different routes.



- 8 -

- 1) Mobile Terminal 160 → BSC/BTS 109 → MSC/VLR 107 → MC 103  
→ Web Emulator 145 of Internet Service Provider (ISP) 140
- 2) Mobile Terminal 160 → IWF 110 → Web Emulator 145
- 3) Computer 150 → Web Emulator 145

For example, in the case of 3), if the computer 150 calls the mobile terminal 170 through the web emulator 145 of the Internet service provider 140, the mobile terminal 170 provides its location information to a GPS (Global Positioning System) service center 130 through an IWF (Interworking Function) 110. Then, the GPS service center 130 transmits the location calculation result to the web emulator 145 of the Internet service provider 140 through the IWF 110.

A remote control client mode and a remote control server mode, operation modes of the mobile terminal according to the present invention, will be defined as follows.

The remote control client mode is activated, when the mobile terminal is connected to an interactive remote control teleservice in SMS Service Option (6/14) after initiating a call (MS Initiated Call). At the moment, the mobile terminal serves as a Client\_T, displays the remote control results performed on a Server\_T on its screen, and transmits user's control information in reply to the remote control results to the Server\_T using the interactive remote control teleservice.

The remote control server mode is activated, when the network calls the mobile terminal (N/W Initiated Call), so that the mobile terminal is connected to the interactive remote control teleservice in the SMS Service Option (6/14). At the moment, the mobile terminal serves as a Server\_T, and is controlled based on to a request from the Client\_T. The Server\_T transmits the remote control result to the Client\_T using the interactive remote control teleservice, instead of displaying it on its LCD (Liquid Crystal Display).

Here, the "interactive remote control teleservice" refers to a service for transmitting/receiving remote control information among the Client\_T, the MC and the Server\_T in a traffic state where a service option configuration of the SMS Service Option (6/14) is used. A brief description of the interactive remote control teleservice will be given below.

- 9 -

The interactive remote control teleservice uses the existing SMS Service Option (6/14) for the service option. In addition, the interactive remote control teleservice uses an interactive remote control teleservice identifier REMOTE\_CONTROL\_TELESERVICE\_ID. The Client\_T, the MC and the Server\_T can trigger an interactive remote control teleservice end procedure, upon failure to receive an ACK until expiration of a specific time period after transmitting SMS submit/deliver messages requesting a user acknowledgement. In another case, however, only the Client\_T can trigger the interactive remote control teleservice end procedure.

The follows are protocol requirements for the interactive remote control teleservice according to the present invention.

1) The interactive remote control teleservice ID REMOTE\_CONTROL\_TELESERVICE\_ID shall be newly defined among reserved teleservice IDs of the SMS protocol. The interactive remote control teleservice ID is used to identify an interactive remote control teleservice SMS message among the Client\_T, the Server\_T and the MC. The interactive remote control teleservice ID among the Client\_T, the Server\_T and the MC is handled based on the web emulator requirements, the mobile terminal requirements and the MC requirements.

2) A remote control menu request identifier specification between the Client\_T and the Server\_T shall be defined. When the Client\_T transmits an SMS message by setting (or filling) a CHARi field of a user message subparameter to (or with) the remote control menu request identifier, the Server\_T transmits user defined remote control menu information or default remote control menu information.

#### Mobile Terminal Requirements for Interactive Remote Control Teleservice

1) The mobile terminal supports a separate remote control mode. The remote control mode is divided into a remote control client mode and a remote control server mode. Fundamentally, the mobile terminal shall be able to operate in both the remote control client mode and the remote control server mode.

2) When the mobile terminal serves as a Server\_T, the mobile terminal

- 10 -

shall be able to register in a remote control menu so that the user can perform the remote control. Therefore, the mobile terminal may provide a user interface. The user interface for registering the remote control menu is optional. When the user interface for registering the remote control menu is not provided, the mobile terminal with the interactive remote control function may use a default menu set by the manufacturer.

3) The mobile terminal has an additional function of handling an interactive remote control teleservice ID for an SMS protocol layer.

10       - When the teleservice ID is REMOTE\_CONTROL\_TELESERVICE\_ID, the mobile terminal shall be able to transmit/receive a CHARi field of the user message subparameter to/from a remote control application (program).

      - In the remote control mode, the mote terminal shall manage SESSION\_SEQ in the following order:

15       a) When the remote control mode is activated, the mobile terminal initializes SESSION\_SEQr and SESSION\_SEQs to 0xFF.

      b) Upon receipt of an SMS deliver message from the MC while SESSION\_SEQs is 0xFF, the mobile terminal stores [(SESSION\_SEQr + 2) modulo 8] as SESSION\_SEQs.

20       c) Upon receipt of an SMS deliver message from the MC while SESSION\_SEQs is not 0xFF, the mobile terminal processes the SMS deliver message if the SESSION\_SEQr is identical to the SESSION\_SEQs. Otherwise, if the SESSION\_SEQr is not identical to the SESSION\_SEQs, the mobile terminal does not process the MSS deliver message. Here, the SESSION\_SEQr represents  
25       SESSION\_SEQ of the SMS deliver message received from the MC, while SESSION\_SEQs represents SESSIO\_SEQ managed in the SMS protocol layer of the mobile terminal in the remote control mode.

      - Upon receipt of an SMS deliver message with an END\_OF\_SESSION field set to '1' while the teleservice ID field is set to  
30       REMOTE\_CONTROL\_TELESERVICE\_ID, the mobile terminal shall transmit a remote control end request to the remote control application.

#### Operation of Remote Control Application

35       - When the remote control application is in the remote control client mode, the mobile terminal (or Client\_T) operates as follows:

      a) Upon receipt of a remote control client mode activation request from the user interface, the mobile terminal activates the remote control client mode.

      b) The mobile terminal transmits information transmitted from the

- 11 -

Server\_T to the user interface.

c) The mobile terminal sets (fills) the CHARi field of the user message subparameter of the teleservice layer to (with) information selected by the user, and the teleservice ID field to REMOTE\_CONTROL\_TELESERVICE\_ID, and then transmits them to the SMS protocol stack.

- When the remote control application is in the remote control server mode, the mobile terminal (or Server\_T) operates as follows:

a) Upon receipt of a remote control server mode activation request from the SMS protocol stack, the mobile terminal activates the remote control server mode.

b) Upon receipt of a remote control menu request while the remote control server mode is activated, the mobile terminal sends a remote control server mode activation request to the user interface by setting the CHARi field of the user message subparameter to the remote control menu request.

c) The mobile terminal generates an event defined by the user interface of the Server\_T based on the control information selected by the Client\_T, and then awaits an ACK from the user interface.

d) Upon receipt of an ACK from the user interface, the mobile terminal sets the CHARi field of the user message subparameter of the teleservice layer to the remote control process result and the teleservice ID field to the REMOTE\_CONTROL\_TELESERVICE\_ID, and then transmits them to the SMS protocol stack.

e) Upon receipt of an interactive remote control teleservice end request from the SMS protocol layer, the mobile terminal ends the interactive remote control teleservice according to an interactive remote control teleservice end procedure.

f) The mobile terminal operating in the remote server mode cannot request an end of the interactive remote control teleservice. However, it is exceptional when the mobile terminal fails to receive an interactive remote control message for a prescribed time.

#### User Interface Requirements

1) Upon receipt of a remote control client mode activation request from the remote control application, the user interface activates the remote control client mode.

2) Upon receipt of a remote control server mode activation request with the CHARi field of the user message subparameter set to the remote control menu

- 12 -

request from the remote control application, the user interface activates the remote control server mode and then transmits the remote control menu to the remote control application.

5           3) When the remote control client mode is activated, the user interface shall display the CHARi of the received user message subparameter on the LCD according to the reply type and method (see Joint Specification for PCS Terminal Manufacturer-SMS function), limit a type of the user ACK, and transmit the user ACK to the remote control application.

10

          4) When the mote control server mode is activated, the user interface transmits the remote control process result to the remote control application by setting the CHARi field of the user message subparameter based on the reply type and method (see Joint Specification for PCS Terminal Manufacturer-SMS function), instead of displaying the result performed on the event generated in the  
15           current state of the user interface.

#### MC Requirements

##### 1) \* and + service number process

20

- The MC recognizes an SMS origination message with a destination address beginning with '\*' as an interactive teleservice and provides a consistent user interface to the Client\_T until the SESSION is ended by the user or the network, and also provides a consistent user interface to the subscriber (or Server\_T) until the session is ended by the user or the network, based on the  
25           service number.

- When the teleservice ID is REMOTE\_CONTROL\_TELESERVICE\_ID, the transport layer of the MC shall provide SMS message exchange service between the mobile terminals using the origination and destination addresses.

30

##### 2) REMOTE\_CONTROL\_TELESERVICE\_ID handling requirements

- When the teleservice ID is REMOTE\_CONTROL\_TELESERVICE\_ID, the MC shall create a unique value S as SESSION\_ID and guarantee independency of the interactive remote control teleservice session by assigning the created unique value to the Client\_T and the Server\_T.

35

- When the teleservice ID is REMOTE\_COTNROL\_TELESERVICE\_ID, the MC shall manage SESSION\_SEQ in the following order.

a) Upon receipt of an SMS origination message with a destination address beginning with '\*', the MC shall initialize SESSION\_SEQr and SESSION\_SEQs

- 13 -

to 0x00 and set SESSION\_SEQ of the SMS deliver message to SESSION\_SEQr.

b) Upon receipt of an SMS submit message, the MC shall set SESSION\_SEQ of the SMS submit message to SESSION\_SEQr and store [(SESSION\_SEQr + 1) modulo 8] as SESSION\_SEQs.

5 c) To transmit an SMS deliver message, the MC sets the SESSION\_SEQ of the SMS deliver message to SESSION\_SEQs. Here, SESSION\_SEQr represents SESSION\_SEQ received with the SMS submit message, while SESSION\_SEQs represents SESSION\_SEQ managed in the SMS protocol layer of the MC in the interactive remote control teleservice.

10 - The MC should be able to connect the Client\_T to the Server\_T on a point-to-point basis during the remote control teleservice session, based on the origination address and the termination address in an SMS point-to-point message parameter.

### 15 Network Requirements

1) The network shall provide an interactive remote control teleservice registration procedure.

20 - The network shall provide an operating procedure registerable in it, in order that all the mobile terminals with the interactive remote control teleservice function can be provided with the interactive remote control teleservice. For example, the interactive remote control teleservice registration procedure can use a method similar to a network registration procedure for a wait-during-call function. When the user presses SEND button after selecting a combination of specified keys, the network shall provide the remote control teleservice to the user,  
25 recognizing that the user desires to be provided with the remote control teleservice.

2) When the user does not register the interactive remote control teleservice, the network should be able to prevent it from connecting the remote control service to the mobile terminal with no remote control teleservice function.

30 A detailed procedure for the network requirements will not be described herein, for simplicity. The MS web emulator requirements should be able to support all the contents corresponding to the Client\_T among the mobile terminal requirements and the user interface requirements.

35 FIG. 5 illustrates a layer structure of a mobile communication system and a message format of each layer according to an embodiment of the present invention. The illustrated layer structure is featured in that a remote control layer

- 14 -

490 exists on the teleservice layer 510 of the IS-637 layer structure shown in FIG. 3. Accordingly, the illustrated layer structure will be called an "IS-637+ layer structure". The remote control layer 490 includes a remote control type field (RC\_TYPE) 501, a result code field (RESULT\_CODE) 502, a security code length field (SEC\_CODE\_LEN) 503, a security code field (SEC\_CODE) 505, a remote control parameter length field (RC\_LEN) 506, and a remote control information parameter field (RC\_PARAMETER) 507. In addition, the remote control layer 490 can further include a supplemental field length field and a supplemental field.

Shown in Tables 1 to 9 are the types and field structure of transport layer and remote control layer messages according to an embodiment of the present invention. Specifically, Tables 1 to 6 show the type and field structure defined in 3.4 Transport Layer Message of IS-637A, and Tables 7 to 9 show the type and field structure of the remote control layer newly defined according to an embodiment of the present invention.

Table 1 shows the type of the transport layer message defined by Table 3.4-1 SMS Transport Layer Message of IS-637. According to Table 1, the current message type MESSAGE\_TYPE includes an SMS Point-to-Point message, an SMS Broadcast message and an SMS Acknowledge message.

Table 1

Message Type	BS → MS	MS → BS	SMS_MSG_TYPE Code
SMS Point-to-Point	X	X	00000000
SMS Broadcast	X		00000001
SMS Acknowledge	X	X	00000010
Reserved			

Tables 2A and 2B show a detailed format of a transport layer message defined by 3.4.1 Message Format of IS-637A. The transport layer message is comprised of one SMS\_MSG\_TYPE field of Table. 2A and at least one record (PARAMETER\_ID field, PARAMETER\_LEN field, and Parameter DATA field) of Table 2B.

Table 2A

Field	Length (bits)
-------	---------------

- 15 -

SMS_MSG_TYPE	8
--------------	---

Table 2B

Field	Length (bits)	Description
PARAMETER_ID	8	This field shall be set to the number of octets in the SMS MSG parameter, not including the PARAMETER_ID and PARAMETER_LEN field
PARAMETER_LEN	8	
Parameter Data	8×PARAMETER_LEN	

- 5 Table 3 shows a message format defined by Table 3.4.2.1-1 SMS Point-to-Point Message Parameters of 3.4.3 Message Definition of IS-637A. Although bearer data is operational in realizing the transport layer, the bearer data, when it is used for the one-sided remote control, shall be newly defined as shown Table 5.

Table 3

Parameter	Type
Teleservice Identifier	Mandatory
Originating Address	Mobile-Terminated Messages: not present Mobile-Originated Messages: Mandatory
Originating Subaddress	Optional
Destination Address	Mobile-Terminated Messages: not present Mobile-Originated Messages: Mandatory
Destination Subaddress	Optional
Bearer Reply Option	Optional
Bearer Data	Optional

10

Table 4 shows a message format defined by Table 3.4.3-1 Parameter Identifiers in 3.4.3 Parameter Definitions of IS-637A.

Table 4

Parameter	PARAMETER_ID Value
Teleservice Identifier	00000000
Broadcast Service Category	00000001
Origination Address	00000010



- 16 -

Originating Subaddress	00000011
Destination Address	00000100
Destination Subaddress	00000101
Bearer Reply Option	00000110
Cause Codes	00000111
Bearer Data	00001000
All other values are reserved	

Table 5 shows a message format defined by 3.4.3.1 Teleservice Identifier of IS-637A, and according to Table 4, PARAMETER\_ID of the Teleservice ID is '00000000'.

5

Table 5

Field	Length (bits)	Description
PARAMETER_ID	8	00000000
PARAMETER_LEN	8	00000010
IDENTIFIER	16	This field shall be set to the value corresponding to the Teleservice, as defined in the SMS_TELESERVICE Identifier Values Table in IS-41_C

Table 6 shows a message format of a sub ID of the Teleservice ID of FIG. 5, defined by 3.4.3.1-1. TIA/EIA-41-D Supported Teleservices of IS-637A. As shown, there are several previously defined Teleservices. Likewise, it is possible to implement remote control of the mobile terminal according to the present invention by defining the remote control teleservice in the reversed field.

10

Table 6

IS-637 Teleservice	IS-41 Teleservice	Value
IS-91 Extended Protocol Enhanced Services	CMT-91	
Cellular Paging Teleservice	CPT-95	4097
Cellular Messaging Teleservice	CMT-95	4098
Voice Mail Notification	VMN-95	4099

15

Table 7 defines the remote control type field TC\_TYPE for the remote control message of the mobile terminal according to an embodiment of the present invention.

Table 7

Parameter	PARAMETER_ID Value
Teleservice Identifier	00000000
Broadcast Service Category	00000001
Origination Address	00000010
Originating Subaddress	00000011
Destination Address	00000100
Destination Subaddress	00000101
Bearer Reply Option	00000110
Cause Codes	00000111
Bearer Data	00001000
All other values are reserved	

FIG. 6A illustrates a format of a user data field of the transport layer, wherein a remote control type field RC\_TYPE in the remote control message of the mobile terminal is '0001', according to an embodiment of the present invention. FIG. 6B illustrates a format of the user data field of the transport layer, wherein the remote control type field in the remote control message of the mobile terminal is '0010', according to an embodiment of the present invention.

Table 8 shows a detailed format of the user data field of the transport layer wherein a remote control type field in the remote control message of the mobile terminal is filled with '0010', according to an embodiment of the present invention.

Table 8

Field	Length	Description
RESULT_CODE	8	Remote control process result state information of the mobile terminal. If RESULT_CODE is not successful, Internet web emulator provides error information to user without performing the remaining fields.
SEC_CODE_LEN	8	Length of SECURITY_CODE (unit:

- 18 -

		octet)
SEC_CODE	8×SECURITY_CODE_LEN	Indicate whether it is possible to perform remote control access to mobile terminal
RC_LEN	8	Length of RC_PARAMETER (unit: octet)
RC_PARAMETER	8×RC_LEN	Remote control information of mobile terminal. In the case of MT (Mobile Termination), event information generated in Internet web mobile terminal is set in a unit of 8 bits. In the case of MO (Mobile Origination), it represents remote control process result information for mobile terminal

In Table 8, RESULT\_CODE represents remote control process result state information of the mobile terminal. If the RESULT\_CODE is not SUCCESS, the Internet web emulator provides error information to the user without performing the remaining fields. SEC\_CODE\_LEN represents a length of SECURITY\_CODE in octet, and SEC\_CODE indicates whether it is possible to perform remote control access to the mobile terminal. RC\_LEN represents a length of RC-PARAMETER in octet. RC\_PARAMETER represents remote control information for the mobile terminal. In the case of MT (Mobile Termination), event information generated in a mobile terminal emulator of the Internet web is set in a unit of 8 bits. In the case of MO (Mobile Origination), the RC\_PARAMETER represents information on the remote control process result for the mobile terminal.

Table 9 shows usage of the RESULT\_CODE of Table 8. For example, if a remote control command is a power-off command, the Server\_T turns off power and sets the RESULT\_CODE to '00000000' while sending a rely to the Client\_T. Unlike other control commands (e.g., phone number search command), the reply

message is not required to include the RC\_PARAMETER field. This is because the Server\_T is simply required to turn off power.

Table 9

RESULT_COD	Description
00000000	Success
00000001	Failure – access item not found
00000010	Failure – security code disagreed
00000011	Failure – no reply from mobile terminal
All other values are reserved.	

5

FIG. 7 illustrates a configuration of a remote control software program executed by a remote control application of the mobile terminal serving as a Client\_T or a Server\_T, according to an embodiment of the present invention. Referring to FIG. 7, a remote control application 750 converts a remote control command received from the Client\_T or the remote control process result to be transmitted by the Server\_T to a user interface signal of the mobile terminal. For example, if the Client\_T (e.g., mobile terminal 160 or computer 150) transmits a remote control command to input a numeric key '1'. The Server\_T (e.g., mobile terminal 170) then analyzes the remote control command and generates a user interface signal as if a numeric key '1' is directly input thereto. A main controller (not shown) of the mobile terminal 170 performs a unique process for input of the numeric key '1', and the process result is provided to the remote control application 750, so that the remote control process result can be reported to the Client\_T. That is, the remote control application 750 triggers the user interface 700 so as to perform such process. A detailed description of the process will be made with reference to FIGs. 9 to 12.

FIGs. 8A and 8B illustrate an operation implemented by the Client\_T in a mobile communication system which, remotely controls a mobile terminal through a SMS call on a one-side basis according to an embodiment of the present invention.

Referring to FIG. 8A, a user of the mobile terminal 160 accesses the Internet service provider (ISP) 140 through the computer 150. The ISP 140 determines in step 801 whether it is accessed by a specific user. If a specific user attempts to access it, the ISP 140 performs a log-in procedure in step 803. The log-in procedure is performed for user authentication and to inform the user of the

- 20 -

process result on a specific operation. If the log-in is failed, the step 801 is repeatedly performed. In the meantime, if the log-in is succeeded, it is determined in step 805 whether remote control for the mobile terminal is selected. The step 805 can be skipped, if the ISP 140 has only a remote control emulator for the mobile terminal. In this case, if the log-in is succeeded in the log-in procedure of step 803, the ISP 140 directly proceeds to step 807. If the log-in is succeed in step 803 or if the MS (mobile terminal) remote control emulator is selected in step 805, the ISP 140 requests the user to select a model, i.e., a type of the mobile terminal in step 807. This is because the mobile terminals may have different user interfaces. The ISP 140 determines in step 809 whether a model of the mobile terminal is selected by the user. If the user has selected a model of the mobile terminal, the ISP 140 drives (or runs) an MS remote control web emulator in step 811. If the MS remote control web emulator is driven, the ISP 140 requests the user to input a security code in step 813. The security code should be identical to a security code previously set in the mobile terminal 160 by the user. After the security code request, the IPS 140 determines in step 815 whether a security code is input by the user. Upon receipt of a security code, the ISP 140 stores the received security code in step 817, and then performs a remote control operation requested by the user. The user will select a key or a menu indicating an intended function displayed on a monitor of the computer 150, using a user interface of the mobile terminal 160.

The ISP 140 recognizes the remote control command, input by the user, from the computer 150 in step 819, and stores the remote control command in step 821. Thereafter, in step 823, the ISP 140 performs an emulation operation according to the remote control command and then returns to step 819. If no more remote control command is received in step 819, the ISP 140 requests in step 825 the user to determine whether to transmit a remote control message for controlling the mobile terminal 170 and then determines whether the user determines to transmit the remote control message. If the user determines the transmission, the ISP 140 creates an RC message including the stored RC type, security code, length of control information and the control information in step 829, and then transmits the created RC message in step 831. After transmitting the RC message, the ISP 140 determines in step 833 whether an ACK message is received in reply to the transmitted message. If an ACK message is not received for a prescribed time period, RC\_TYPE is not '0010', or a result code of the received remote control message is not '00000000' (i.e., not successful), the ISP 140 displays an error on the web emulator in step 839. Then, the user can recognize occurrence of

- 21 -

an error at the sight of the information displayed in the computer 150.

However, upon receipt of an ACK message in reply to the transmitted message in step 833, the ISP 140 provides the control command process result to the computer 150 in step 835. Thereafter, the ISP 140 determines in step 837 whether to perform another remote control operation by checking a key input by the user. If it is determined to perform another remote control operation, the ISP 140 returns to step 819, and otherwise, returns to step 807. Meanwhile, if the user determines not to transmit a remote control message in step 825, the ISP 140 deletes the information stored up to then in step 827, and returns to step 807.

The present invention has been described with reference to an environment where the user accesses the ISP 140 through the computer 150. However, the invention can also be performed through another mobile terminal accessible to the ISP 140.

FIG. 9 illustrates an operation performed by the Server\_T in a mobile communication system, which remotely controls a mobile terminal through a SMS call on a one-side basis according to an embodiment of the present invention.

Referring to FIG. 9, the mobile terminal 170 detects user data of the teleservice layer from a received SMS message in step 901, and then detects an RC message by decapsulating the user data in step 903. After decapsulating the user data, the mobile terminal 170 initializes the result code RESULT\_CODE to '11111111'. After the decapsulation, the mobile terminal 170 determines in step 905 whether the user data is successfully decapsulated. If the user data is not successfully decapsulated, the mobile terminal 170 sets the result code RESULT\_CODE to a value '00000001' indicating decapsulation failure in step 929. In contrast, if the user data is successfully decapsulated, the mobile terminal 170 analyzes the RC\_TYPE field indicating the type of the RC message in step 907, to determine whether the user data is an SMS service message or an RC message. If the RC\_TYPE field is set to '0001', the user data is an SMS message. Otherwise, if the RC\_TYPE field is set to '0010', the user data is an RC message. As the result of the analysis, if the user data is an SMS message, the mobile terminal 170 performs a normal SMS user data processing procedure in step 930. However, if the user data is an RC message, the mobile terminal 170 detects a security code from a security code field of the RC message in step 909. Subsequently, in step 911, the mobile terminal 170 compares the security code detected in step 909 with

- 22 -

a security code previously set by the user, to determine whether they are identical, i.e., whether the user intended to perform the remote control is an authenticated user. As the result of the comparison, if the security code detected from the security code field in the RC message is identical to the preset security code, the mobile terminal 170 proceeds to step 913, and otherwise, proceeds to step 931. In step 931, the mobile terminal 170 sets the RESULT\_CODE to '00000010' indicating authentication failure. In step 913, the mobile terminal 170 detects a length of the RC parameter from the RC parameter length field RC\_LEN of the RC message. The RC parameter length is identical to the number of RC parameters divided by octet, i.e., 8 bits. That the length of the RC parameter is 'i' means that the RC parameter is analyzed i times in a unit of 8 bits. That is, the mobile terminal 170 sets the detected RC parameter length RC\_LEN to RC\_PARAMETER<sub>r</sub>[i] and then performs steps 915 to 921 and 933. This operation is repeated i times. Specifically, in step 915, the mobile terminal 170 determines whether the i value is less than the detected RC parameter length RC\_LEN. Here, an initial i value is '0'. If the i value is larger than the RC parameter length, the mobile terminal proceeds to step 925, and otherwise, proceeds to step 917. In step 917, the mobile terminal 170 increases the i value by 1. After increasing the i value by 1, the mobile terminal 170 analyzes an i<sup>th</sup> RC parameter divided by 8 bits and executes a control command corresponding to the i<sup>th</sup> RC parameter, in step 919. After executing the control command, the mobile terminal 170 determines in step 921 whether the control command is successfully executed. If the control is successfully performed, the mobile terminal 170 sets the RESULT\_CODE to '00000000' in step 933, and then returns to step 915. However, if the remote control is failed in step 921, the mobile terminal 170 sets the RESULT\_CODE to a value indicating control failure in step 923.

In step 927, the mobile terminal 170 creates an RC message for informing the user of the control result. In the RC message, RC\_TYPE field is set to '0010', RESULT\_CODE field is set to the result code determined in the above process, SEC\_CODE\_LEN field is set to '00000000', and RC\_LEN is also set to '00000000'. The created RC message is encapsulated as user data of the teleservice layer and then transmitted to the user through the SMS service, in step 927.

FIGs. 10A to 10D illustrate states displayed on a screen of the remote control requesting terminal (Client\_T 160 or computer 150) according to an embodiment of the present invention. Specifically, FIG. 10A illustrates a screen

- 23 -

state when the remote control mode is selected, and FIG. 10B illustrates a screen on which a Remote Control Main Menu is displayed after the remote control mode is selected in FIG. 10A. Further, FIG. 10C illustrates a screen on which a Phone Management Menu is displayed, and FIG. 10D illustrates a screen on which the execution result of a remote control command "Locking" from the Server\_T is displayed.

FIG. 11 illustrates an operating procedure of the MS web emulator for interactive remote control according to an embodiment of the present invention. Here, the mobile terminal serves as a Client\_T. Of course, the operating procedure of FIG. 11 can be implemented using a computer.

Referring to FIG. 11, a user accesses a web site provided by the ISP 140 of FIG. 4 in step 1110. Here, the "user" refers to a user of the computer 150 or the mobile terminal 160, which serves as the Client\_T. If a log-in procedure is successfully performed in step 1111, the Client\_T drives an MS web emulator in step 1112. The Client\_T inputs a phone number of the Server\_T (e.g., a phone number of the mobile terminal 170) and then attempts to set up a call to the Server\_T, in step 1113. A process for connecting the web emulator 145 to the MC 103 is similar to a general connection process between the web server and the MC, so a detailed description will not be made. Call setup requirements of the MC 103 and the Server\_T are based on a call processing method in the remote control client mode and a call processing method in the remote control server mode.

The Client\_T checks in step 1114 whether a call is successfully set up. If the call is successfully set up, the Client\_T proceeds to step 1115. However, if the call is failed, the Client\_T outputs a call failure message in step 1120 and then returns to step 1113. If the call is successfully set up, the Client\_T transmits a remote control command to the Server\_T in step 1115, and then awaits a reply from the Server\_T for a reply waiting time in step 1116. For example, the remote control command may include a menu list (e.g., a list including phone book and message management) request.

Upon receipt of a reply from the Server\_T, i.e., ACK and process result within the reply waiting time in step 1116, the Client\_T proceeds to step 1117. However, upon failure to receive the reply from the Server\_T, the Client\_T ends the call in the same method as when the user requests the remote control end, in step 1121, and then proceeds to step 1120. Here, if the remote control command



- 24 -

was a menu list request command, the "process result" means the requested menu list. The Client\_T performs emulation according to the reply result from the Server\_T and then awaits the user operation, in step 1117. Here, if the remote control command was a menu list request command, the "emulation" means  
5 outputting the menu list.

The Client\_T determines in step 1118 whether the remote control is completed. If the remote control is not completed, the Client\_T returns to step 1115. In other words, at the sight of the menu list, the user will select a specific  
10 menu (e.g., phone book) and searches its submenu (e.g., search by name), performing the remote control. For this operation, the Client\_T should return to step 1115. However, when the user selects remote control end, the Client\_T performs in step 1119 a call end process in the same method as when the user requests a remote call end.

15

FIG. 12 illustrates an operating procedure of a mobile terminal (Server\_T) for interactive remote control according to an embodiment of the present invention. Referring to FIG. 12, the Server\_T determines in step 1210 whether a call is set up. If a call is set up, the Server\_T detects the RC\_TYPE field from the received SMS  
20 message and determines whether the detected value represents that the SMS message or a remote control message, in step 1211. If the RC\_TYPE does not represent a remote control message, the Server\_T performs a normal SMS process in step 1217.

25

However, if the RC\_TYPE represents a remote control message, the Server\_T analyzes the remote control message and converts the analyzed remote control message to an MS user interface signal, in step 1212. Then, a controller of the Server\_T may recognize the remote control command as a control command received through its user interface. In step 1213, the Server\_T creates a remote  
30 control message and transmits the created remote control message. Thereafter, the Server\_T checks in step 1214 whether a reply is received within a reply waiting time. Upon receipt of a reply within the reply waiting time, the Server\_T returns to step 1211. Otherwise, upon failure to receive a reply within the reply waiting time, the Server\_T ends the call in step 1215 and then transitions to an idle mode  
35 in step 1216. Here, the "reply" does not mean the actual remote control command process result, but a reply option (ACK) of the transport layer. Meanwhile, if it is determined in step 1210 that a call is not set up, the Server\_T also transitions to the idle mode in step 1216.

- 25 -

FIG. 13 is a ladder diagram illustrating a call process method among a mobile terminal operating in the remote control client mode, an SMS center, an MC, a base station and an MSC according to an embodiment of the present invention.

In step [1], the user selects a remote control mode so that the mobile terminal serves as a Client\_T in order to perform remote control. In step [2], a user interface displays Remote Control Mode on its display unit as shown in FIG. 10A, and then awaits a destination address input by the user. In step [3], the user inputs a destination address of the Server\_T and then presses SEND button. In step [4], the user interface transmits SMS Service Option (6/14) to the signaling layer to request connection of the SMS Service Option. In step [5], the signaling layer transmits an origination message to the BSC/BTS along with the SMS Service Option (6/14). In step [6], the BSC/BTS transmits an extended channel assignment message (ECAM) to the Client\_T to establish a dedicated channel to the user interface, and makes a connection in the SMS Service Option through service negotiation. In step [7], if the Client\_T is connected in the SMS Service Option (6/14), the signaling layer informs the user interface of connection of the SMS Service Option (6/14). In step [8], if the mobile terminal is in the remote control mode, the user interface informs the remote control application of connection of the SMS Service Option (6/14), and sends a remote control client mode activation request to the remote control application by setting the CHARi field of the user message subparameter to a remote control menu request and a destination address to a service number (\*, +) of Server\_T. The reference RCA\_C indicates the remote control application of Client\_T. In step [9], the remote control application is activated into the remote control client mode, sets the CHARi field of the user message subparameter to a remote control menu request, a destination address to a service number (\*, +) of the Server\_T, and a teleservice ID field to REMOTE\_CONTROL\_TELESERVICE\_ID, and then transmits them the SMS protocol stack. In step [10], the SMS protocol stack transmits an SMS submit message to the MC after setting the CHARi field of the user message subparameter to a remote control menu request, a destination address to a service number (\*, +) of the Server\_T, the teleservice ID field to REMOTE\_CONTROL\_TELESERVICE\_ID, and the USER\_ACK\_REQ field in a reply option subparameter to '1'.

Here, the SMS protocol stack recognizes the SMS origination message

- 26 -

with a destination address beginning with '\*' as an interactive teleservice, and transmits the SMS submit message of the interactive remote control teleservice. Even after the message transmission, the SMS protocol stack awaits an SMS deliver message from the network, instead of returning to the idle mode. The  
5 mobile terminal starts a remote control session as soon as the SMS submit message is transmitted.

FIG. 14 is a ladder diagram illustrating a call processing method among a mobile terminal operating in the remote control server mode, an SMS center, a call  
10 processing center, a base station and an MSC according to an embodiment of the present invention.

In step [11], the MC/MSC detects the current location of the Server\_T based on SMS Service Option (6/14) and a service number of the Server\_T, and  
15 sends a request for connection with the Server\_T to the BTS/BSC where the Server\_T is located. In step [12], the BTS/BSC transmits a general page message to the Server\_T, and the Server\_T transmits a page ACK message to the BSC/BTS along with the SMS Service Option (6/14). In step [13], the BSC/BTS establishes a dedicated channel to a user interface by transmitting an extended channel  
20 assignment message (ECAM) to the Server\_T, and makes a connection in the SMS Service Option (6/14) through service negotiation. In step [14-1], the BSC/BTS informs the MC/MSC that the dedicated channel is established to the user interface of the Server\_T. In step [14-2], a call processor of the Server\_T informs the user interface of connection of the SMS Service Option. In step [15],  
25 the MC transmits the SMS submit message received from the Client\_T to the Server\_T as an SMS deliver message.

The MC transmits the SMS deliver message to the Server\_T after setting the CHARi field of the user message subparameter to a remote control menu  
30 request, the teleservice ID to REMOTE\_CONTROL\_TELESERVICE\_ID, the origination address to a service number of the Client\_T, the SESSION\_ID to a unique value [S], the SESSION\_SEQ field to '0', and the USER\_ACK\_REQ to '1'. Upon receipt of an SMS submit message in which an initial teleservice ID is set to REMOTE\_CONTROL\_TELESERVICE\_ID, the MC should create a unique  
35 value [S] to distinguish the SESSION\_ID from the other sessions, and can use the SESSION\_ID in addressing the Client\_T and the Server\_T.

In step [16], if the teleservice ID of the received SMS deliver message is

- 27 -

REMOTE\_CONTROL\_TELESERVICE\_ID, the SMS protocol stack of the Server\_T sets the CHARi field of the user message subparameter to a remote control menu request, and transmits it to the remote control application. In step [17], the remote control application activates the remote control server mode, and then sends a remote control activation request to the user interface by setting CHARi of the user message subparameter to a remote control menu request. In step [18], when CHARi of the user message subparameter is set to a remote control menu request, the user interface sets the CHARi field of the user message subparameter to remote control menu information available for remote control, and the reply type and method (see Joint Specification for PCS Terminal Manufacturer-SMS function) to Menu, transmits them to the remote control application, and then awaits a user reply in the Remote Control Men. In step [19], the remote control application sets the CHARi field of the user message subparameter to remote control menu information, the reply type and method (see Joint Specification for PCS Terminal Manufacturer-SMS function) to Menu, and the teleservice ID to REMOTE\_CONTROL\_TELESERVICE\_ID, and then transmits them to the SMS protocol stack.

The mobile terminal may previously set the remote control menu information. When the remote control menu is not set, the mobile terminal may operate in a default menu.

FIGs. 15A to 15C are ladder diagrams illustrating an actual interactive remote control teleservice process according to an embodiment of the present invention.

Referring to FIG. 15A, in step [20], the SMS protocol stack transmits an SMS submit message to the MC by setting the CHARi field of the user message subparameter to the remote control menu information, the teleservice ID to REMOTE\_CONTROL\_TELESERVICE\_ID, the SESSION\_ID to a unique value [s], the SESSION\_SEQ field to a received value (0), the reply type and method to Menu, and the USER\_ACK\_REQ to '1'. The remote control menu provided by the Server\_T will be assumed as follows.

Remote Control Main Menu  
1: Phone Book  
2: Bell/Vibration/Volume  
3: Electronic Diary

- 28 -

## 4: Phone Management

In step [21], the MC transmits an SMS deliver message to the Client\_T by setting the CHARi field of the user message subparameter to remote control menu information, the teleservice ID to REMOTE\_CONTROL\_TELESERVICE\_ID, the SESSION\_ID to a unique value [S], the SESSION\_SEQ field to [(SESSION\_SEQr + 1) modulo 8], the reply type and method to Menu, and USER\_ACK\_REQ to '1' based on the SESSION\_ID (unique value [S]) of the received SMS submit message. In step [22], upon receipt of the SMS deliver message from the MC, the SMS protocol stack of the Client\_T transmits the remote control menu information and the CHARi of the user message subparameter if the teleservice ID is REMOTE\_CONTROL\_TELESERVICE\_ID. In step [23], the remote control application transmits the received message to the user interface, since it is in the remote control client mode. In step [24], since the reply type and method of the received message is set to Menu, the user interface awaits user's input after displaying 'Remote Control Main Menu' and '1: Phone Book, 2: Bell/Vibration/Volume, 3: Electronic Diary, 4: Phone Management' on its display as shown in FIG. 10B, and setting a digit input mode. Here, the "digit input mode" refers to a user interface operation mode where the user can input only arrow keys and digit keys.

Next, a description will be made of an operation of steps [25] to [38] in which the user reply is '4'.

In step [25], the user selects '4' as a reply. In step [26], since the user interface is in the remote control client mode, it sets the CHARi field of the user message subparameter to '4' and then transmits it to the remote control application. In step [27], the remote control application sets the CHARi field of the user message subparameter to '4' and the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, and then transmits them to the SMS protocol stack. In step [28], the SMS protocol stack transmits an SMS submit message to the MC by setting the CHARi field of the user message subparameter to '4', the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, the SESSION\_ID to the unique value [S], the SESSION\_SEQ to a received value (1), the USER\_ACK\_REQ to '1'. In step [29], the MC transmits the SMS submit message received from the Client\_T to the Server\_T as an SMS deliver message by setting the CHARi field of the user message subparameter to '4', the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, the SESSION\_ID to

- 29 -

a unique value [S], the SESSION\_SEQ field to SESSION\_SEQs, and the USER\_ACK\_REQ to '1'. In step [30], upon receipt of the SMS deliver message from the MC, the SMS protocol stack of the Server\_T transmits the CHARi field of the user message subparameter filled with '4' to the remote control application, if the teleservice ID is REMOTE\_COTROL\_TELESERVICE\_ID. In step [31], the remote control application of the Server\_T awaits a reply form the user interface after generating the same event as if the user of the Server\_T inputs a '4'-key according to a definition of the user interface based on the value '4' in the CHARi field of the user message subparameter. At the moment, the user interface waits user's input in the remote control menu. In step [32], since the user interface in the remote control server mode, it replies to the remote control application by setting the CHARi field of the user message subparameter to Phone Management Menu and the reply type and method to Menu, instead of displaying the selected submenu 'Phone Management'.

The remote control menu provided by the Server\_T will be assumed as follows.

#### Phone Management Menu

- 1: Power Off
- 2: Locking
- 3: Emergency Call

In step [33], the remote control application sets the CHARi of the user message subparameter to Phone Management Menu, the reply type and method to Menu, and the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, and then transmits them to the SMS protocol stack. In step [34], the SMS protocol stack sets the CHARi of the user message subparameter to Phone Management Menu, the reply type and method to Menu, the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, the SESSION\_ID to the unique value [S], the SESSION\_SEQ field to SESSION\_SEQs, and the USER\_ACK\_REQ to '1', and transmits them to the MC. In step [35], the MC transmits the SMS submit message received from the Server\_T to the Client\_T as an SMS deliver message by setting the CHARi field of the user message subparameter to Phone Management Menu, the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, the SESSION\_ID to the unique value [S], the SESSION\_SEQ field to SESSION\_SEQs, and the USER\_ACK\_REQ to '1'. In step [36], upon receipt of the SMS deliver message from the MC, the SMS

- 30 -

protocol stack of the Client\_T analyzes the SESSION\_ID and the SESSION\_SEQ and then transmits the CHARi of the user message subparameter set to Phone Management Menu, if the teleservice ID is REMOTE\_COTROL\_TELESERVICE\_ID. In step [37], the remote control application transmits the received message to the user interface, since it is in the remote control client mode. In step [38], since the reply type and method of the received message is set to Menu, the user interface waits user's input after displaying 'Phone Management Menu' and '1: Power Off, 2: Locking, 3: Emergency Call' and then setting the user interface to the digit input mode.

Next, a description will be made of an operation of steps [39] to [52] in FIGs. 15A and 15B, in which the user reply is '2'.

In step [39], the user selects '2' as a reply. In step [40], the user interface sets the CHARi field of the user message subparameter to '2' and transmits it to the remote control application. In step [41], the remote control application sets the CHARi field of the user message subparameter to '2' and the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, and transmits them to the SMS protocol stack. In step [42], the SMS protocol stack transmits an SMS submit message to the MC by setting the CHARi field of the user message subparameter to '2', the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, the SESSION\_ID to the unique value [S], the SESSION\_SEQ field to the SESSION\_SEQs, and the USER\_ACK\_REQ to '1'. In step [43], the MC transmits the SMS submit message received from the Client\_T to the Server\_T as an SMS deliver message by setting the CHARi field of the user message subparameter to '2', the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, the SESSION\_ID to the unique value [S], the SESSION\_SEQ field to SESSION\_SEQs, and the USER\_ACK\_REQ to '1'. In step [44], upon receipt of the SMS deliver message from the MC, the SMS protocol stack of the Server\_T analyzes the SESSION\_ID and the SESSION\_SEQ and then transmits it to the remote control application if the teleservice ID is REMOTE\_COTROL\_TELESERVICE\_ID. In step [45], the remote control application of the Server\_T generates the same event as when the user of the Server\_T inputs the '2'-key according to a definition of the user interface based on the value '2' in the CHARi field of the user message subparameter, and then awaits a reply from the user interface. At the moment, the user interface awaits a user's reply in the Phone Management Menu.

- 31 -

In step [46], since the user interface is in the remote control server mode, it performs a 'Locking' operation, and then sets the CHARi to 'Locked' and sends it to the remote control application as a reply, instead of displaying the operation result on the LCD. In step [47], the remote control application sets the CHARi of the user message subparameter to 'Locked' and the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, and transmits them to the SMS protocol stack. In step [48], the SMS protocol stack sets the CHARi of the user message subparameter to 'Locked', the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, the SESSION\_ID to the unique value [S], the SESSION\_SEQ field to SESSION\_SEQs, and USER\_ACK\_REQ to '1', and transmits them to the MC. In step [49], the MC transmits the SMS submit message to the Client\_T as an SMS deliver message by setting the CHARi of the user message subparameter to 'Locked', the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, the SESSION\_ID to the unique value [S], the SESSION\_SEQ field to SESSION\_SEQs, and the USER\_ACK\_REQ to '1'. In step [50], upon receipt of the SMS deliver message from the MC, the SMS protocol stack of the Client\_T analyzes SESSION\_ID and the SESSION\_SEQ, and then transmits the CHARi of the user message subparameter filled with 'Locked' to the remote control application, if the teleservice ID is REMOTE\_COTROL\_TELESERVICE\_ID. In step [51], since the remote control application is in the remote control client mode, it transmits the received message to the user interface. In step [52], the user interface awaits user's input after displaying 'Locked' on its display as shown in FIG. 10D. In step [53], if the user selects Remote Control Menu Request, the procedure proceeds to step [54], and if the user selects Remote Control End, the procedure proceeds to step [69].

Next, a description will be made of an operation of steps [54] to [68] shown in FIG. 15C, in which the user selects Remote Control Menu Request.

In step [54], the user selects Remote Control Menu Request. In step [55], when the mobile terminal is in the remote control mode, the user interface sets the CHARi field of the user message subparameter to Remote Control Menu Request and transmits it to the remote control application. In step [56], the remote control application sets the CHARi of the user message subparameter to Remote Control Menu Request and the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, and then transmits them to the SMS protocol stack. In step [57], the SMS protocol stack transmits an SMS submit message to the MC by setting the CHARi of the user message subparameter to



- 32 -

Remote Control Menu Request, the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, the SESSION\_ID to the unique value [S], the SSESSION\_SEQ field to SESSION\_SEQs, and the USER\_ACK\_REQ to '1'. In step [58], the MC transmits the SMS submit message received from the Client\_T to the Server\_T as an SMS deliver message by setting the CHARi field of the user message subparameter to Remote Control Menu Request, the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, the SESSION\_ID to the unique value [S], the SESSION\_SEQ field to the SESSION\_SEQs, and the USER\_ACK\_REQ to '1'. In step [59], upon receipt of the SMS deliver message from the MC, the SMS protocol stack of the Server\_T analyzes the SESSION\_ID and the SESSION\_SEQ, and then transmits them to the remote control application if the teleservice ID is REMOTE\_COTROL\_TELESERVICE\_ID. In step [60], the remote control application of the Server\_T generates the same event as when the user of the Server\_T inputs a Remote Control Menu Request key according to a definition of the user interface based on the CHARi field of the user message subparameter filled with Remote Control Menu Request, and then awaits a reply from the user interface. At the moment, the user interface awaits a user's reply in Initial Screen after locking the mobile terminal.

In step [61], since the user interface is in the remote control server mode, it performs MS Locking operation, and then sets the CHARi field to Remote Control Menu Information and transmits it to the remote control application as a reply, instead of displaying the execution result on the LCD. In step [62], the remote control application sets the CHARi of the user message subparameter to Remote Control Menu and the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, and transmits them to the SMS protocol stack. In step [63], the SMS protocol stack sets the CHARi of the user message subparameter to Remote Control Menu, the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, the SESSION\_ID to the unique value [S], the SESSION\_SEQ to SESSION\_SEQs, and the USER\_ACK\_REQ to '1'. In step [64], the MC transmits the SMS submit message received from the Server\_T to the Client\_T as an SMS deliver message by setting the CHARi of the user message subparameter to Remote Control Menu, the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, the SESSION\_ID to the unique value [S], the SESSION\_SEQ field to the SESSION\_SEQs, and the USER\_ACK\_REQ to '1'. In step [65], upon receipt of the SMS deliver message from the MC, the SMS protocol stack of the Client\_T analyzes the SESSION\_ID and the SESSION\_SEQ and then transmits the CHARi of the user message subparameter

- 33 -

filled with Remote Control Menu to the remote control application, if the teleservice ID is REMOTE\_COTROL\_TELESERVICE\_ID. In step [66], since the remote control application is in the remote control client mode, it transmits the received message to the user interface. In step [67], the user interface waits a user's input after displaying 'Remote Control Main Menu' and '1: Phone Book, 2: Bell/Vibration/Volume, 3: Electronic Diary, 4: Phone Management' on its display as shown in FIG. 10B, and setting the digit input mode. In step [68], if the user selects Remote Control End as a reply, then the procedure proceeds to step [69].

FIG. 16 is a ladder diagram illustrating an operation according to an embodiment of the present invention in which a user requests Remote Control End.

In step [69], the user inputs an END button. In step [70], the user interface sends a remote control end request to the remote control application. In step [71], the remote control application sets the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, and then sends a remote control end request to the SMS protocol stack. In step [72], the SMS protocol stack transmits an SMS conversation end message to the MC by setting the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, the SESSION\_ID to the unique value [S], the SESSION\_SEQ to SESSION\_SEQs, the END\_OF\_SESSION to '1' and the USER\_ACK\_REQ to '1', and then awaits an SMS conversation end ACK message. In step [73-1], upon receipt of a remote control end ACK, the SMS protocol stack sends a remote control end confirm to the remote control application if the teleservice ID is REMOTE\_COTROL\_TELESERVICE\_ID. In step [74-1], upon receipt of the remote control end confirm from the user interface, the remote control application informs the user interface of an end of the remote control, and then returns to a previous mode of a state where the remote control client mode activation mode is activated. In step [75-1], the user interface transmits an interactive remote control teleservice call end request for the SMS Service Option (6/14) to a call processor. In step [76-1], the call processor releases SMS SO (6/14) call, sends a call end confirm to the user interface, and then transitions to an idle mode. Further, the user interface returns to its initial screen. In step [73-2], upon receipt of an SMS conversation end message from the Client\_T, the MC transmits an SMS remote control end message to the Server\_T by setting the teleservice ID to REMOTE\_COTROL\_TELESERVICE\_ID, the SESSION\_ID to the unique value [S], the SESSION\_SEQ to SESSION\_SEQs, and the USER\_ACK\_REQ to '1'. In step [74-2], upon receipt of the SMS remote control end message from the MC, the SMS protocol stack of the Server\_T

- 34 -

analyzes the SESSION\_ID and the SESSION\_SEQ, and then sends a remote control end request to the remote control application, if the teleservice ID is REMOTE\_COTROL\_TELESERVICE\_ID. In step [75-2], the remote control application of the Server\_T generates the same event as when the user of the Server\_T inputs an END key according to a definition of the user interface in response to the received remote control end request, and then returns to a previous mode of a state when the remote control mode is activated. In step [75-2], the user interface transmits an SMS SO (6/14) interactive remote control teleservice call end request to the call processor. In step [76-2], the call processor releases an SMS SO (6/14) call, sends a call end confirm to the user interface, and then transitions to the idle mode. Thereafter, the user interface returns to its initial screen.

As described above, the present invention enables the user to control his or her mobile terminal at a remote place and access information stored in the mobile terminal through an interactive remote control service. Therefore, even when the user loses or fails to carry the mobile terminal, he or she can control the mobile terminal at the remote place. When the invention is provided with the GPS service, it is also possible to detect a location of the mobile terminal by performing mobile origination for the GPS service even at a remote place. Therefore, when the mobile terminal or a child carrying the mobile terminal is missing, the user can easily recognize the place where the missing mobile terminal or child is located. In addition, the user can turn off or lock the mobile terminal at a remote place. Besides, the user can also access such information as a specific phone number stored in the mobile terminal. In other words, the user can freely control all the functions of the mobile terminal even at the remote place. In addition, it is also possible to provide a remote diagnostic service.

While the invention has been shown and described with reference to a certain preferred embodiment thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the invention as defined by the appended claims.

- 35 -

**WHAT IS CLAIMED IS:**

1. A system for remotely controlling a mobile terminal in a mobile communication system, comprising:  
5 the mobile terminal for receiving a control command through a call link and performing an operation according to the received control command; and  
an Internet service provider including a remote control emulator, for transmitting a mobile terminal remote control command to the mobile terminal through the call link upon receipt of the mobile terminal remote control command  
10 through a user interface of the remote control emulator.
2. The system as claimed in claim 1, wherein the call link is a voice call link.
- 15 3. The system as claimed in claim 1, wherein the call link is an SMS (Short Message Service) call link.
4. The system as claimed in claim 1, wherein the call link is a data call link.  
20
5. The system as claimed in claim 1, wherein the mobile terminal transmits a remote control process result to the Internet service provider through the call link.
- 25 6. The system as claimed in claim 1, wherein the user is connected to the Internet service provider through another mobile terminal.
7. The system as claimed in claim 1, wherein the user is connected to the Internet service provider through a computer.  
30
8. The system as claimed in claim 1, wherein the mobile terminal operates based on an IS-637+ layer structure in which a remote control layer exists on a teleservice layer.
- 35 9. The system as claimed in claim 8, wherein the remote control layer includes a remote control type field indicating whether a character field of user data of a teleservice layer represents an SMS message or a remote control message, a result code field indicating a remote control process result for the

- 36 -

mobile terminal, a security code length field, a security code field indicating whether remote control access to the mobile terminal is available, a remote control parameter length field, and a remote control information parameter field.

5           10.     The system as claimed in claim 1, wherein the web emulator operates based on an IS-637+ layer structure in which a remote control layer exists on a teleservice layer.

10           11.     The system as claimed in claim 10, wherein the remote control layer includes a remote control type field indicating whether a character field of user data of a teleservice layer represents an SMS message or a remote control message, a result code field indicating a remote control process result for the mobile terminal, a security code length field, a security code field indicating whether remote control access to the mobile terminal is available, a remote control  
15           parameter length field, and a remote control information parameter field.

20           12.     The system as claimed in claim 1, wherein the mobile terminal includes a remote control application for converting a remote control command or a remote control process result to a user interface signal of the mobile terminal.

20           13.     A method for remotely controlling a mobile terminal through an Internet service provider connected to a mobile communication system providing a short message service, comprising the steps of:

25           (a) driving an mobile terminal web emulator by logging in through a client terminal;

            (b) setting up a call by inputting a phone number of a remote server terminal after driving the mobile terminal web emulator;

30           (c) outputting a remote control main menu provided by the remote server terminal through the set call and transmitting a remote control command to the remote control server; and

            (d) performing emulation according to a reply, upon receipt of the reply from the remote control server within a prescribed time.

35           14.     The method as claimed in claim 13, further comprising the steps of:

            determining whether the remote control is completed;

            ending the call, when the remote control is completed; and

            returning to the step (c), when the remote control is not completed.

- 37 -

15. A mobile terminal comprising:
- 5 a user interface having a remote control application which is activated in a remote control client mode when an origination call is connected to an interactive remote control teleservice in an SMS service option, and is activated in a remote control server mode when a call from a network is connected to the interactive remote control teleservice in the SMS service option.




FIG.1




FIG.2






FIG.3

4/20





FIG. 4

5/20

FIG.5



RC_TYPE	SMS USER DATA
---------	---------------

FIG.6A

RC_TYPE	RESULT_CODE	SEC_CODE_LEN	SEC_CODE	RC_LEN	RC_PARAMETER
---------	-------------	--------------	----------	--------	--------------

FIG.6B

7/20





FIG. 7

8/20

FIG. 8A



9/20





FIG.8B

10/20

FIG.9





11/20




FIG.10A




FIG.10B

12/20




FIG.10C




FIG.10D




FIG.11

14/20




FIG.12

15/20




FIG.13




FIG.14

17/20




FIG.15A

18/20




FIG.15B



19/20




FIG.15C




FIG.16

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/KR02/00085

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7 H04Q 7/20

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: H04M, H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

KR, JP: IPC as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 9811744 A1 (NOKIA TELECOMMUNICATIONS OY) 19 MARCH 1998 see abstract, claim 1, figure 1, page 2, line 23 - page 3, line 8	1-15
Y	US 5 046 082 A (GTE MOBILE COMMUNICATIONS SERVICE CORPORATION) 3 SEPTEMBER 1991 see abstract, col3, line 11 - line 39, claims 1, 8-9, 19-24, 30	1-15
A	KR 1998-027702 A (SK TELECOM CO. LTD.) 15 JULY 1998 see abstract, claims 1, 7-8, 12	8-15
P, A	JP 2001-086228 A (HITACHI KOKUSAI ELECTRIC INC.) 30 MARCH 2001 see the whole document	12-14

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

07 MAY 2002 (07.05.2002)

Date of mailing of the international search report

08 MAY 2002 (08.05.2002)

Name and mailing address of the ISA/KR



Korean Intellectual Property Office  
920 Dunsan-dong, Seo-gu, Daejeon 302-701,  
Republic of Korea

Facsimile No. 82-42-472-7140

Authorized officer

KANG, Hae Seong

Telephone No. 82-42-481-5739



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/KR02/00085

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9811744 A1	19-03-1998	US 6321257 BA FI 963659 A FI 103546 B1 JP 2000501270 T2 EP 861565 A1 AU 4304197 A1	20-11-2001 17-03-1998 15-07-1999 02-02-2000 02-09-1998 02-04-1998
US 5 046 082 A	03-09-1991	NONE	
KR 1998-027702 A	15-07-1998	NONE	
JP 2001-086228 A	30-03-2001	EP 1083764 A2 EP 1083764 A3 KR 2001-0050386 A	14-03-2001 02-05-2001 15-06-2001

Form PCT/ISA/210 (patent family annex) (July 1998)